

HLP New Product Information Sheet.

Solar DC Isolator Switch - SI25-CBX2M25

Model: SI25-CBX2M25

- HLP Controls is pleased to release the **NEW IMO European made SOLAR DC ISOLATOR.**
- This unit can switch single strings up to 4KW & twin strings up to 7KW.
- Simple 2 wire connection, **NO LINKS, NO JUMPERS.**
- Large enclosure with plenty of room for cables.
- Has 2 x 25mm threaded entries top & bottom.
- Take solar cable up to 16mm² in it's box terminals with no special tools required.
- Don't take the risk with any inferior products. Many other units have failed in the field and caused massive recalls.
- More than 1,000,000 of the IMO DC Isolators have been installed world-wide without a failure.
- Fully waterproof, outside rated and fully APPROVED.
- For wiring advice call us. We also have a range of **larger DC Isolators, String Combiners** and **Zero Power Export Control** units available for all sizes of system.



Specifications:

- Suitable for solar systems using 1 or 2 strings with a maximum of 20 panels per string;
- Maximum KW for 1 string 4KW;
- Maximum KW for 2 strings 7KW;
- Rated at a maximum of 25A;
- Rated at a maximum of 1500V per pole;
- Insulation 8KV;
- Switch position is visible from a distance;
- Pad-lockable in OFF position;
- Waterproof and weatherproof;
- Australian wording label included.

HLP Controls

Phone: 1800 500 160

Fax: 1800 827 160

Email: sales@hlpcontrols.com.au

Web: www.hlpcontrols.com.au

Bar code: 9005738857897

November 2014